



- CONNECTOR MATES WITH ANY 15 POSN PLUG IN AMPLIMITE SERIES & COMPLIES WITH AMP SPEC 108-40005 WHERE APPLICABLE.
- MOLDED PARTS: FLAME RETARDANT 94V-0 RATED THERMOPLASTIC, BLACK.
SHELL: CARBON STEEL.
CONTACTS: PHOSPHOR BRONZE.
EYELETS: BRASS.
SCREWLOCKS: ZINC.
INSERTS: ZINC.
- SHELL: TIN PLATED.
CONTACTS: .000030 GOLD FOR A DISTANCE OF .100 MIN FROM MATING END, TIN PLATED .000100-.000200 ON OPPOSITE END, ALL OVER .000050 NICKEL.
EYELETS: TIN PLATED.
SCREWLOCKS: CLEAR CHROMATE.
INSERTS: CLEAR CHROMATE.

25-06334

| | |
|-------------------|-------------|
| FEMALE SCREWLOCKS | 5745782-6 |
| THREADED INSERTS | 5745782-4 |
| NONE | 5745782-2 |
| MOUNTING HARDWARE | PART NUMBER |

**COPYRIGHT 2005
TE CONNECTIVITY CORP
ALL RIGHTS RESERVED**

| | | | | | |
|--|--|--------------------------------|--|---|--|
| THIS DRAWING IS A CONTROLLED DOCUMENT. | | DIN A FERNANDEZ-DOCKS 04-06-05 | | TE Connectivity | |
| DIMENSIONS: INCHES | | CHK S BOLASH 04-06-05 | | RCPT ASSY, SIZE 2, 15 POSN, RTANG, AMPLIMITE HD-20, WITH METAL SHELL, WITH OR WITHOUT SCREWLOCKS OR INSERTS | |
| TOLERANCES UNLESS OTHERWISE SPECIFIED: | | APVD M WALMSLEY 04-06-05 | | NAME | |
| 0 PLC ± - | | PRODUCT SPEC | | 108-40025 | |
| 1 PLC ± - | | APPLICATION SPEC | | 114-40010 | |
| 2 PLC ± - | | SIZE | | A1 | |
| 3 PLC ± .005 | | CAGE CODE | | 00779 | |
| 4 PLC ± .005 | | DRAWING NO | | 5745782 | |
| ANGLES ± ° | | WEIGHT | | - | |
| MATERIAL | | FINISH | | CUSTOMER DRAWING | |
| | | SCALE | | 4:1 | |
| | | SHEET | | 1 OF 1 | |
| | | REV | | R | |